

**DigelAir**  
HVAC SUPPLY

1-21 Grenfell Crescent  
Nepean, Ontario K2G 0G3

Phone: (613) 723-0359

Fax: (613) 226-4892

Email: [sales@digelair.com](mailto:sales@digelair.com)

Web Page: [www.digelair.com](http://www.digelair.com)

# TOYOTOMI

## 3/4-TON Portable Conditioner

### AIR-COOLED COMMERCIAL RENTAL UNIT



- This unit is rated to provide 8,000 btu/h cooling capacity.
- Electrical: 115/1/60 volts, 7.6 MCA, 15 amp breaker.
- Unit weight: 58 pounds.
- Unit dimensions: 11.5" W x 14.75" D x 34.5" H
- Separate fan motors (evaporator & condenser).
- Oscillating louvers for even distribution of conditioned air.
- Maximum exhaust duct length is 10 ft. 5 inch flex.
- Automatic shut-off when condensate tank is full, or an optional external condensate pump can be installed.

#### **APPLICATION:**

The unit is placed inside the room to be cooled.

The condenser exhaust is ducted outside of the room, either through a window, through the wall, or up into the ceiling building return air plenum.

Window vent kit included with unit.



**TOYOTOMI**  
COOLING-HEATING PRODUCTS

Window panel extensions are available for oversize windows, or patio doors. In commercial buildings where the space above the t-bar ceiling tiles acts as the return air plenum for the central air conditioning system, exhaust the warm air as shown here. Or the unit can also be vented out through the wall (like a dryer vent). The maximum condenser duct length is 10 feet of 5inch flex.

